







Max. load weight «G» for different lift combinations

Method of lift									
Number of legs	1	1	2	2	2		3 - 4		
Angle of inclination	0°	90°	0°	90°	0 - 45°	45 - 60°	0 - 45°	45 - 60°	
Thread d1	M8	1	0.5	2	1	0.7	0.5	1.05	0.5
	M10	1.5	0.9	3	1.8	1.26	0.9	1.89	0.9
	M12	1.5	1.3	3	2.6	1.82	1.3	2.73	1.3
	M14	2.6	1.8	5.2	3.6	2.52	1.8	3.78	1.8
	M16	2.8	2.3	5.6	4.6	3.22	2.3	4.83	2.3
	M18	2.5	2.3	5	4.6	3.22	2.3	4.83	2.3
	M20	2.8	2.5	5.6	5	3.5	2.5	5.25	2.5
	M22	6	4.5	12	9	6.3	4.5	9.45	4.5
	UNC 1/4"	0.4	0.2	0.81	0.4	0.28	0.2	0.42	0.2
	UNC 5/16"	1	0.54	2	1.09	0.76	0.54	1.14	0.54
	UNC 3/8"	1.45	0.72	2.9	1.45	1.01	0.72	1.52	0.72
	UNC 1/2"	1.54	1.27	3.09	2.54	1.78	1.27	2.67	1.27
	UNC 5/8"	2.81	2.22	5.63	4.45	3.11	2.22	4.67	2.22
	UNC 3/4"	2.81	2.38	5.63	4.77	3.34	2.38	5.01	2.38
	UNC 7/8"	6.13	4.45	12.27	8.9	6.23	4.45	9.35	4.45