









Max. load weight «G» for different lift combinations

Method of lift										
Number of legs	1	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4
Angle of inclination	0°	90°	0°	90°	0-45°	45-60°	asymm.	0-45°	45-60°	asymm.
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1
Thread d1	M12	M12	M12	M12	M12	M12	M12	M12	M12	M12
	M16	M16	M16	M16	M16	M16	M16	M16	M16	M16
	M20	M20	M20	M20	M20	M20	M20	M20	M20	M20
	M24	M24	M24	M24	M24	M24	M24	M24	M24	M24
	M30	M30	M30	M30	M30	M30	M30	M30	M30	M30
	M36	M36	M36	M36	M36	M36	M36	M36	M36	M36
	0.63	0.63	1.26	1.26	0.88	0.63	0.63	1.32	0.95	0.63
	1.5	1.5	3.0	3.0	2.1	1.5	1.5	3.15	2.25	1.5
	2.5	2.5	5.0	5.0	3.5	2.5	2.5	5.25	3.75	2.5
	4.0	4.0	8.0	8.0	5.6	4.0	4.0	8.4	6.0	4.0
	6.7	5.0	13.4	10.0	7.0	5.0	5.0	10.5	7.5	5.0
	10.0	8.0	20.0	16.0	11.2	8.0	8.0	16.8	12.0	8.0