



DIN 6330B

Sechskantmutter

1,5 d hoch, vergütet, Festigkeitsklasse 10. Mit kugeligem Ende verwendbar direkt zu Kegelpfanne DIN 6319D oder G. Mit dem flachen Ende verwendbar zu Scheiben DIN 6340.



	Größe	E	M	R	S	VE	Gewicht [g]
	M6	11,05	9	9	10	100	5
	M8	14,40	12	12	13	100	9
	M10	17,80	15	15	16	50	14
	M10	18,90	15	15	*17	50	20
	M12	20,03	18	17	18	50	20
	M12	21,10	18	17	*19	50	28
	(M14)	23,40	21	20	21	50	34
	(M14)	24,50	21	20	*22	50	45
	M16	26,80	24	22	24	50	58
	(M18)	30,10	27	24	27	25	83
	M20	33,50	30	27	30	25	110
	(M22)	37,70	33	30	34	10	185
	(M22)	35,70	33	30	*32	10	130
	M24	40,00	36	32	36	10	195
	(M27)	45,60	40	36	41	-	280
	M30	51,30	45	41	46	-	405
	M36	61,30	54	50	55	-	715
	M42	72,60	63	58	65	-	1170
	M48	83,90	72	67	75	-	1800

* Alte DIN-Norm.
() DIN erweitert.

Zubehör und Empfehlungen



DIN 6379,
Seite 96



DIN 787,
Seite 92



DIN 6340,
Seite 107

CAD

