









# Max. load weight «G» for different lift combinations

Method of lift											
Number of legs	1	1	2	2	2		2	3 / 4		3 / 4	
Angle of inclination	0°	90°	0°	90°	0-45°	45-60°		0-45°	45-60°	unsym.	
Thread d1	<b>M36</b>	15.0	8.0(10.0)	30.0	16.0(20.0)	11.2(14.0)	8.0(10.0)	8.0(10.0)	16.8(21.0)	12.0(15.0)	8.0(10.0)
	<b>M42</b>	17.0	12.0(13.0)	34.0	24.0(26.0)	16.8(18.0)	12.0(13.0)	12.0(13.0)	25.2(27.3)	18.0(19.5)	12.0(13.0)
	<b>M48</b>	18.0	13.0(16.0)	36.0	26.0(32.0)	18.2(22.4)	13.0(16.0)	13.0(16.0)	27.3(33.6)	19.5(24.0)	13.0(16.0)
	<b>M56</b>	28.0	16.0(22.0)	56.0	32.0(44.0)	22.4(30.8)	16.0(22.0)	16.0(22.0)	33.6(46.2)	24.0(33.0)	16.0(22.0)
	<b>M64</b>	28.0	16.0(25.0)	56.0	32.0(50.0)	22.4(35.0)	16.0(25.0)	16.0(25.0)	33.6(52.5)	24.0(37.5)	16.0(25.0)