









SAFETY FACTOR 4:1

Lifting method									
Number of legs	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4
Inclination angle β	90°	0°	90°	0-45°	>45-60°	Asymm.	0-45°	>45-60°	Asymm.
Load factor	1	2	2	1.4	1	1	2.1	1.5	1

Safety factor 4:1 for max. total load weight in tonnes, tightened and aligned in direction of pull

ACP M 12 / 1/2"	1.35	2.7	2.7	1.9	1.35	1.35	2.84	2	1.35
ACP M 16 / 5/8"	2.5	5	5	3.5	2.5	2.5	5.25	3.75	2.5
ACP M 20 / 3/4"	4	8	8	5.6	4	4	8.4	6	4
ACP M 24 / 1"	6.3	12.6	12.6	8.8	6.3	6.3	13.2	9.5	6.3
ACP M 30 / 1 1/4"	8	16	16	11.2	8	8	16.8	12	8

Safety factor 4:1 for max. total load weight in lbs, tightened and aligned in direction of pull

ACP M 12 / 1/2"	4400	5940	5940	4158	2970	2970	6237	4455	2970
ACP M 16 / 5/8"	8800	11000	11000	7700	5500	5500	11550	8250	5500
ACP M 20 / 3/4"	13200	17600	17600	12320	8800	8800	18480	13200	8800
ACP M 24 / 1"	17600	27720	27720	19404	13860	13860	29106	20790	13860
ACP M 30 / 1 1/4"	26400	35200	35200	24640	17600	17600	36960	26400	17600

Working load limit in tonnes (top) and in lbs (bottom).

Subject to technical modifications.