









# Max. load weight «G» for different lift combinations

Method of lift											
Number of legs		1	1	2	2	2 metric		2	3 / 4 metric		
Angle of inclination		0°	90°	0°	90°	0-45°	45-60°	asymm.	0-45°	45-60°	asymm.
Factor		2	1	4	2	1.4	1	1	2.1	1.5	1
Thread d1											
	<b>M 8</b>	0.6	0.3(0.4)	1.2	0.6(0.8)	0.42(0.56)	0.3(0.4)	0.3(0.4)	0.63(0.84)	0.45(0.6)	0.3(0.4)
	<b>M10</b>	0.9	0.45(0.6)	1.8	0.9(1.2)	0.63(0.84)	0.45(0.6)	0.45(0.6)	0.95(1.26)	0.68(0.9)	0.45(0.6)
	<b>M12</b>	1.2	0.6(0.75)	2.4	1.2(1.6)	0.84(1.05)	0.6(0.75)	0.6(0.75)	1.26(1.58)	0.9(1.12)	0.6(0.75)
	<b>M16</b>	2.6	1.3(1.5)	5.2	2.6(3.0)	1.82(2.1)	1.3(1.5)	1.3(1.5)	2.73(3.15)	1.95(2.25)	1.3(1.5)
	<b>M20</b>	4.0	2.0(2.5)	8.0	4.0(5.0)	2.8(3.5)	2.0(2.5)	2.0(2.5)	4.2(5.25)	3.0(3.75)	2.0(2.5)
	<b>M24</b>	7.0	3.5(4.0)	14.0	7.0(8.0)	4.9(5.6)	3.5(4.0)	3.5(4.0)	7.35(8.4)	5.25(6.0)	3.5(4.0)
	<b>M30</b>	10.0	5.0(6.0)	20.0	10.0(12.0)	7.0(8.4)	5.0(6.0)	5.0(6.0)	10.5(12.6)	7.5(9.0)	5.0(6.0)